

# Coastal Nomad Drifter



## Quick Start Guide



SouthTEK Sensing Technologies S.L. 2013.  
Copyright © All right reserved

For more details, please refer to [www.southteksl.com](http://www.southteksl.com)

## Key features

- Cost-effective drifter
- Coastal applications
- User friendly software
- Robust, precise and handy
- GPS, GLONASS and GALILEO tracking
- GSM coverage and communications
- Flexible deployment: from an infratable boat to an aircraft carrier
- Continuous working mode up to several months depending on user configured intervals for transmission and position sampling

SouthTEK Sensing Technologies S.L. is not responsible for any direct or indirect damages resulting from the use of these devices

## Everyday use of the Nomad drifter

### Turning on the drifter

1. Unscrew cap from the floater.
2. Disconnect the dummy plug (this will automatically switch on the drifter) and set the rubber protection in place.
3. Screw cap firmly onto floater, hand tight, ensuring proper seating of the gasket around its entire circumference.
4. The buoy is now ready for deployment. Please confirm proper communications through the web application: <http://ldmanager.southteksl.com>
5. To switch off the drifter just connect the dummy plug.

## Charging the internal battery

6. Plug the charger.

The status light on the charger indicates charging status (red charging, green charged).

Once the internal battery has finished charging, the NOMAD is ready for use.

The LiPo batteries are sent at 40% of capacity. Fully charge the batteries before deployment.

**Caution!**  
Users of Lithium polymer (LiPo) batteries should take extreme care when handling such batteries. Legislation regarding disposal of LiPo batteries vary from country to country.

## LD Manager Application

6 Logging in web application  
<http://ldmanager.southteksl.com>

SouthTEK Sensing Technologies LD Manager

Username \*  
Password \*  
Remember me  
Log in


Forgot your password?  
Forgot your username?

Site Map | Terms and Conditions | © SouthTEK 2016

LD Manager app available on Play Store



## Specifications



<b>GSM</b>	Quad-Band GSM 850/900/1800/1900 MHz
<b>GPRS</b>	Multi-slot class 12
<b>GNSS</b>	Receiver 32 channels
	GPS/GALILEO/SBAS: L1 1575.42 MHz GLONASS: L1 1597.5 MHz
<b>Processor</b>	ARM Core
<b>Memory</b>	5 MB (RAM) and 10 MB (Flash)
<b>Battery</b>	Lithium polymer (LiPo) Capacity standard 20400 mAh (Type M) Nominal = 3.7V
<b>Antennas</b>	Iridium: 2 dBi GNSS: 2.5 dBi
<b>Charging conditions</b>	DC 4.2V 2A max
<b>Dimensions</b>	72 cm x 22 cm x 22 cm
<b>Weight</b>	2895 gr

## LED Indicators

- Started (Running or idle mode).
- Searching (GNSS and comm. signals).
- Error (Device anormal functionality).

### LED indicators.

For a detailed description of led flashing pattern, please refer to Application Note #202 at <http://www.southteksl.com/index.php/downloads>

## Accesories



## 7

### Main screen of LD Manager LDManager v2.1.5

**Devices**

Model	Id	Status	Power	RC	EC	CED	ARC	AEC	ACRD	Actions
Coastal NOMAD-B	LCA00018	●	30%	2047	2	2016-03-31				
Coastal NOMAD-D	LCA00019	●	34%	2044	120	2016-03-31				
Coastal NOMAD-M	LCA00020	●	37%	2044	120	2016-03-31				

Buttons: Refresh, Events & alarms, Configure device, Search mode, Update software, Switch off, Data available, Export data

Devices info

Communications info

Actions

**User menu**

- Notifications
- Reports

**User info**

User: user@mail.com

**User information**

Display # 20

Click Notifications button: you can include your e-mail to receive the alarms generated by the device. Location of last position acquired

### 1 Status

- Started.
- Started with warnings.
- Startup error.
- Online
- Offline
- Lapsed
- Online with warning

### 4 Configure device

- Configure device
- Config change in process (with motion)
- Error changing config

Battery life will depend on GSM coverage and sampling/transfer interval.

### 2 Battery power

- Full battery
- Medium battery
- Low battery
- Very low battery

- RC** Remaining connections
- EC** Estimated consumption (conns/hour)
- CED** Credit expiration date

**Configure device**

Buttons: Save, Cancel

**Schedule tab panes:**  
Choose the Sample interval and Transfer interval. Click on the SAVE button to save the configuration.

Sample interval: 5 minutes  
Transfer interval: 10 minutes

**Device info:**  
Id: LCA00075  
IMEI: 353438090331862  
Model: Coastal NOMAD-B  
Top-up date: 2019-04-01  
Device status: Online

**Current config:**  
Sample interval: 5 minutes  
Transfer interval: 10 minutes

### 5 Search mode

SEARCH MODE can be activated or deactivated through LD Manager (below figure) or sent by e-mail (right figure). It becomes operational after the first connection with the drifter.

SEARCH MODE transfers the drifter position via email every five minutes (default) or other user-defined interval.

**Search mode**

Buttons: Apply, Deny, Cancel

Schedule

Id: LCA00018

Sample interval: 5 minutes

Recipient email:

### Activation/deactivation SEARCH MODE through LDManager:

Activate SEARCH MODE to recover easily the drifter including the recipient email and click on Apply button.

Deactivate SEARCH MODE clicking on Deny button.

### Activation/deactivation SEARCH MODE from e-mail:

Send an e-mail to: config@ldmanager.southteksl.com

To activate -> Message:

search on, DRIFTER ID, PASSWORD, SAMPLE INTERVAL\* (in sec)

To deactivate -> Message:

search off, DRIFTER ID, PASSWORD


**Send an email**

Email Address: search on, LCA00018, 1234, 300

Subject:

Message: config@ldmanager.southteksl.com

### 8 Data available



### 6 Alarms: Events & alarms

- Enabled
- Disabled
- Alarms notified

#### Zone alarm:

Notifies exit or entry in the area chosen by the user. Insert coordinates or use the map tool chose the area of interest.

**Events & alarms**

Name	Low battery alarm	Very low battery alarm	Zone alarm	Position request response	Low credit alarm	Credit expiration alarm
LCA00030	●	●	●	●	●	●
LCA00037	●	●	●	●	●	●
LCA00063	●	●	●	●	●	●
LCA00084	●	●	●	●	●	●
LCA00156	●	●	●	●	●	●

### Coordinates

**Configure**

North (add.dddd°): 43

West (add.dddd°): -47

East (add.dddd°): -22

South (add.dddd°): 28

Buttons: Notify exit, Notify entry

### Map tool



- Software version OK.
- Software update request not allowed.
- New software version available.
- Soft. version update in progress (with motion).
- Error updating software version.

### 9 Export data

**Export data**

Report name:

Initial date & hour: [Clear]

Final date & hour: [Clear]

Devices: LCA00030, LCA00037, LCA00063, LCA00084

File format: Plain text (.txt), Spread sheet (.xls), 3D Position (.kml), Matlab file (.mat), GPX file (.gpx)

- Include the Report name.
- Select the initial and final date for data export.
- Choose the Devices for data export.
- Choose file format for data export.